

HDMI to Analog Audio Converter

User manual

Thank you for purchasing this product. For optimum performance and safety, please read these instructions carefully before connecting, operating or adjusting this product. Please keep this manual for future reference.

■ Introduction

This HDMI to Analog Audio Converter is designed for either home or professional audio switching. It converts digital HDMI signals to analog L/R audio and available for connection to an external device such as an amplifier via standard RCA-style jacks and an headphone via an earphone jacks. This Converter is small in size and quite easy to install.

■ Features

- 1、Converts HDMI digital audio signals to analog L/R audio
- 2、Support PCM
32K,44.1K,48K,88.2K,96K,176.4K,192KHz sample
frequency audio
- 3、Provides electromagnetic-noise-free transmission.
- 4、Compliant with HDMI1.3.
- 5、Easy to install and simple to operate.

■ Package

- | | |
|-----------------------------------|------|
| 1. HDMI to Analog Audio Converter | 1PCS |
| 2. USB to mini USB Cable | 1PCS |
| 3. Operation Manual | 1PCS |

■ Specifications

| | |
|-----------------------|-----------------------------|
| Input Ports | 1 x HDMI Female port. |
| Output Port | 1x RCA, 1x headphone |
| Dimensions (mm) | 66(D) x55(W) x20(H) |
| Weight (g) | 40 |
| Operating Temperature | 0°C ~ 40°C / 32°F ~ 104°F |
| Storage Temperature | -20°C ~ 60°C / -4°F ~ 140°F |





■ Operation controls and Functions

Please study the panel drawings below and become familiar with the signal input(s), output(s) and power requirements.

Back Panel:

Top Panel:

Front Panel:



1. Connect a source such as a Blue-Ray Player, game console, A/V Receiver, Cable or Satellite Receiver, etc. to the Converter HDMI input.

2. Connect an amplifier or headphone to the audio output on the Converter.

3. Power on the device and display.

Attention: The converter is a low-power product, it can work normally in most cases. But when the source power is not enough, the converter may work in abnormal condition, the audio output may be flicker. In this condition, please connect the USB cable from the convert mini USB port to source equipment USB port for Power in.

■ Connect diagram

